


SYNTEKO RE-COVER



Synteko RE-COVER is oxidative hardening maintenance oil for periodic maintenance and heavy cleaning of oiled wood and parquet floors. For indoor use only. ReCover conserves, cleans and improves floors treated with one-component natural oil, hardwax oil and two-component oil systems. EC1+ compliant!

AREA OF USE: for periodic maintenance of oiled floors

PRODUCT PROPERTIES:

- oxygen curing
- faintly smelling
- ready to use

COVERAGE:

- 40-80 m²/l, depending on tools and wood species

TOOLS:

- Rubber spatula, 300-500 mm width or roller with 5-8 mm pile high
- Buffing machine (2 adjustments, 150 and 300 r.p.m., if possible)
- For application of Synteko ReCover we recommend high quality red and white pads
- Non-flocculent cotton cloth or trowel for polishing (3pcs/ 20m²)
- clean tools with White Spirit

TECHNICAL DATA:

BASE MATERIAL	Urethane modified pinewood oil, n-Paraffin C5-20 50 -60 %
SOLIDS CONTENT	Approx. 38%
SOLVENT	Aromatic free white spirit
VOC	616 g /l (EU limit value for this product (cat. A/f): 700 g/l (2010) 2004/42/CE
DENSITY	Approx. 780 kg/m ³
FIRE HAZARDS	Flammable class 3. Flash point +65°C
DRYING TIME	Approx. 3-8 hours after buffing
STORAGE	Store frost-free. Best to be stored between +5°C and +30°C Not sensitive to frost
SELF LIFE	24 months in unopened container from production date (s. package)
PACKAGE SIZE	1L

BEFORE USING THE FLOOR

- Do not use vapour-proof, non-skid underlays or other coverings
- Attach felt pads to the legs of chairs and tables in order to avoid scratching the finish.

ATTENTION!

- Vacuum or dry-mop floors regularly
- Be sure to start regular maintenance before the surface is worn through to bare wood or darker walking tracks become visible
- **NB!** Place all organic materials like polishing cloth as well as polishing pads in a metal container filled with water for at least 16 hours to avoid self-combustion. Dispose of them according to regulations.

SYNTEKO RE-COVER

DIRECTIONS FOR USE



For periodic maintenance of floors treated with Synteko oils, always use **Synteko RE-COVER**. How often you use it will depend on the amount of traffic and how often the floor is cleaned:

- normally every other year for residential areas
- approx. 2–4 times per year for commercial areas.

Regular maintenance will restore the lustre of the floor and keep it looking beautiful.

Be sure to begin regular maintenance before you wear through to the bare wood. You can also use RE-COVER for local repairing.

3. PREPARATION

- Clean the floor with a Synteko Remover (s. separate Product Information) solution.
- Make sure the floor is completely dry before applying Synteko Re-Cover.
- Protect the floor from direct sunlight and keep off all underfloor heating from day before application till 24 hours after application
- Shake the container before use for 30-60 seconds. Do not dilute the oil

1. Maintenance procedure for slightly soiled floors

- Apply it thinly with a rubber spatula, roller or white buffing pad
- Allow the floor to absorb the RE-COVER for 10–15 minutes before applying it again (if necessary).
- Apply Synteko RE-COVER maintenance oil sparingly on the surface and work it into the wood with a cotton cloth or a buffer with a white pad. Let the surface dry for 20 minutes.
- Continue buffing until the floor appears to be saturated and no more drops or smears are visible. Work systematically on an area of 10-15 m² at a time, and ensure the overlaps are buffed carefully. Replace dirty cloths or pads as required
- The floor may be used after 3–4 hours, preferably leave overnight

2. Maintenance procedure for heavily soiled floors

- Apply Synteko RE-COVER maintenance oil generously and work it into the wood with a red pad. If the red pad does not give the desired effect, gradually increase the abrasion level of the pads
- Clean off the dirty oil completely
- When the floor appears to be clean and saturated, apply a new thin layer of Arboritec Satin Oil maintenance, and buff with a white pad until no more drops or smears appear
- Allow a minimum of 8 hours drying time before use, preferably leave overnight. Do not use the floor during this period

HEALTH & SAFETY INFORMATION

FOR PROFESSIONAL USE ONLY! Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet) www.synteko.com. The following only represents a selection of important information.

RISK OF SELFIGNITION! CONTAINS DRYING OIL. COLLECT AND KEEP SPILLAGES, USED RAGS ETC IN FIREPROOF CONTAINER AND DESTROY.

Warning! EUH 066 Repeated exposure may cause skin dryness or cracking.

H304 May be fatal if swallowed and enters airways. P280 Wear protective gloves / protective clothing / eye protection / face protection. P303+P361+P353 IF ON SKIN (or hair): Remove / Take off immediately all

contaminated clothing. Rinse skin with water / shower. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor.

P331 Do NOT induce vomiting. P405 Store locked up. P501 Dispose of contents / container to an approved recipient of hazardous waste.

Contains: n-Paraffin C5-20 50 -60 %

Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

Produced by **Synteko AB**
Olof Wijksväg 9, Jörlanda,
Sweden, Tel. +46 303 563 30
www.synteko.com

Date: 01.04.2022