

SYNTEKO RE-COVER

1620



Synteko RE-COVER is a maintenance oil for periodic maintenance of hardwood and cork floors treated with Synteko floor oils

AREA OF USE: for periodic maintenance of oiled floors

PRODUCT PROPERTIES:

- oxygen curing
- faintly smelling
- ready to use
- non-yellowing

COVERAGE:

- 50-100 m²/l, depending on tools and wood species

TOOLS:

- Rubber spatula, 300-500 mm width or flexible stainless steel spatula 250-300 mm width
- Buffing machine (2 adjustments, 150 and 300 r.p.m., if possible)
- Red pad (1pcs/ 20m²)
- Non-flocculent cotton cloth or trowel for polishing (3pcs/ 20m²)
- clean tools with white spirit (UK)/mineral spirits (USA)

TECHNICAL DATA:

BASE MATERIAL	Alkyd ester
SOLIDS CONTENT	Approx. 77%
SOLVENT	Aromatic free white spirit (UK) / mineral spirit (USA)
DENSITY	Approx. 910 kg/m ³ (8,64 lbs./gal US)
FIRE HAZARDS	Flammable. Flash point +40°C (104°F)
DRYING TIME	Approx. 2-4 hours
STORAGE	Store frost-free. Must be stored between +5°C and +30°C (+50°F and +86°F)
SELF LIFE	24 months in unopened container from production date (s. package)
PACKAGE SIZE	1L

BEFORE USING THE FLOOR

- Do not use vapour-proof, non-skid underlays or other coverings
- Attach felt pads to the legs of chairs and tables in order to avoid scratching the finish.

ATTENTION!

- Vacuum or dry-mop floors regularly
- Be sure to start regular maintenance before the surface is worn through to bare wood.
- **NB!** Place all organic materials like cloth in a metal container filled with water for at least 16 hours to avoid self-combustion. Dispose of them according to regulations.

SYNTEKO RE-COVER

DIRECTIONS FOR USE



For periodic maintenance of floors treated with Synteko oils use **Synteko RE-COVER**. How often you use it will depend on the amount of traffic and how often the floor is cleaned:

- normally every other year for residential areas
- approx. 2–4 times per year for commercial areas.

Regular maintenance will restore the lustre of the floor and keep it looking beautiful.

Be sure to begin regular maintenance before you wear through to the bare wood. You can also use RE-COVER for local repairing.

1. PREPARATION

- Clean the floor with a Synteko REMOVER (see separate Product Information) solution.
- Make sure the floor is completely dry before applying Synteko RE-COVER.

2. APPLICATION

- Apply it thinly with a rubber spatula, floor cloth or similar.
- Allow the floor to absorb the RE-COVER for 10–15 minutes before applying it again (if necessary).
- Let the surface dry for 20 minutes.
- Polish the floor with a clean, dry, non-flocculent floor cloth.
- The floor may be used after 2–4 hours.

HEALTH & SAFETY INFORMATION

FOR PROFESSIONAL USE ONLY! Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet) www.synteko.com. The following only represents a selection of important information.

RISK OF SELFIGNITION! CONTAINS DRYING OIL. COLLECT AND KEEP SPILLAGES, USED RAGS ETC IN FIREPROOF CONTAINER AND DESTROY.



Warning! Flammable liquid and vapour. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Call a POISON CENTER or doctor/physician if you feel unwell. Keep cool. Dispose of contents and container in accordance with all local, regional, national or international regulations. Hazardous ingredients: Naphtha (petroleum), hydrotreated heavy. Contains: Butanone oxime. May produce an allergic reaction. Repeated exposure may cause skin dryness and cracking.

Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

Producer:
Synteko AB, Olof Wijksväg 9, Jörlanda, Sweden, Tel. +46 303 563 30
www.synteko.com

Date: 11.2021