

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **product identifiers**

Article No. (user): 486196
Trade name/designation: Classic XD 50 semigloss

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses:

paint and/or paint related material
Reserved for industrial and professional use.

Uses advised against:

Do not use for injecting or spraying.

1.3. **Details of the supplier of the safety data sheet**

supplier (manufacturer/importer/downstream user/distributor)

Synteko AB
Olof Wiksväg 9 Telephone: +46 303 56 330
444 65 Jörlanda
Sweden

Department responsible for information:

Laboratory
E-mail: info@synteko.com

1.4. **Emergency telephone number**

Estonia+372 7943794
Latvia +371 670 42473
Lithuania +370 85 2362052
Finland 0800 147111
Slovenia 112
Croatia +385 123 48342
Romania +40 2131 83606
United Kingdom +44 121 5074123
Germany +49 700 24112112
Poland +48 4225 38400
Czech Republic +420 224 919293
Slovakia +421 25477 4160

UFI: XXXX-XXXX-XXXX-XXXX

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

| | | |
|----------------------|-----------------------------------|------------------------------------|
| Flam. Liq. 3 / H226 | Flammable liquids | Flammable liquid and vapour. |
| Skin Irrit. 2 / H315 | Skin corrosion/irritation | Causes skin irritation. |
| Eye Dam. 1 / H318 | Serious eye damage/eye irritation | Causes serious eye damage. |
| STOT SE 3 / H336 | STOT-single exposure | May cause drowsiness or dizziness. |

2.2. **Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

| | |
|------|------------------------------------|
| H226 | Flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H336 | May cause drowsiness or dizziness. |

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 2 / 11

P280 Wear protective gloves and eye/face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/ physician.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazard components for labelling

2-methylpropan-1-ol
1-methoxy-2-propanol

Supplemental hazard information

EUH208 Contains phthalic anhydride; Fatty acids, C14-18 and C16-18-unsatd., maleated. May produce an allergic reaction.

2.3. Other hazards

Other information

Read label before use. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description Alkyd urea precondensate

Classification according to Regulation (EC) No 1272/2008 [CLP]

| EC No. | REACH No. | weight-% |
|------------------|--|-----------------|
| CAS No. | Designation | |
| Index No. | classification // Remark | |
| 203-539-1 | 01-2119457435-35-XXXX | |
| 107-98-2 | 1-methoxy-2-propanol | 25 - 50 |
| 603-064-00-3 | Flam. Liq. 3 H226 / STOT SE 3 H336 | |
| 201-148-0 | 01-2119484609-23-XXXX | |
| 78-83-1 | 2-methylpropan-1-ol | 7,5 - 10 |
| 603-108-00-1 | Flam. Liq. 3 H226 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H336 | |
| 200-578-6 | 01-2119457610-43-XXXX | |
| 64-17-5 | Ethanol | 2,5 - 5 |
| 603-002-00-5 | Flam. Liq. 2 H225 | |
| 204-436-4 | 01-2119980933-25-XXXX | |
| 120-93-4 | 2-imidazolidone | 2,5 - 5 |
| | Eye Irrit. 2 H319 / STOT RE 2 H373 | |
| 288-306-2 | 01-2119976378-19-XXXX | |
| 85711-46-2 | Fatty acids, C14-18 and C16-18-unsatd., maleated | 0,25 - 0,5 |
| | Skin Irrit. 2 H315 / Skin Sens. 1 H317 | |
| 201-607-5 | 01-2119457017-41-XXXX | |
| 85-44-9 | phthalic anhydride | 0,1 - 0,25 |
| 607-009-00-4 | Acute Tox. 4 H302 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Resp. Sens. 1 H334 / Skin Sens. 1 H317 | |

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 3 / 11

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 4 / 11

empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

WEL, TWA: 375 mg/m³; 100 ppm

WEL, STEL: 560 mg/m³; 150 ppm

Remark: (may be absorbed through the skin)

2-methylpropan-1-ol

Index No. 603-108-00-1 / EC No. 201-148-0 / CAS No. 78-83-1

WEL, TWA: 154 mg/m³; 50 ppm

WEL, STEL: 231 mg/m³; 75 ppm

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

WEL, TWA: 1920 mg/m³; 1000 ppm

phthalic anhydride

Index No. 607-009-00-4 / EC No. 201-607-5 / CAS No. 85-44-9

WEL, TWA: 4 mg/m³

WEL, STEL: 12 mg/m³

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 50,6 mg/kg

DNEL acute inhalative (local), Workers: 553,5 mg/m³

DNEL long-term inhalative (systemic), Workers: 369 mg/m³

DNEL long-term dermal (systemic), Consumer: 18,1 mg/kg

DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m³

DNEL long-term exposure oral (systemic effects), Consumer: 3,3 mg/kg

2-methylpropan-1-ol

Index No. 603-108-00-1 / EC No. 201-148-0 / CAS No. 78-83-1

DNEL short-term oral (acute), Workers:

DNEL long-term oral (repeated), Workers:

DNEL long-term inhalative (local), Workers: 310 mg/m³

DNEL long-term inhalative (local), Consumer: 55 mg/m³

DNEL long-term exposure oral (systemic effects), Consumer: 25 mg/kg

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

DNEL long-term dermal (systemic), Workers: 888 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 500 mg/m³

DNEL long-term dermal (systemic), Consumer: 319 mg/kg bw/day

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 5 / 11

DNEL long-term inhalative (systemic), Consumer: 89 mg/m³
DNEL long-term exposure oral (systemic effects), Consumer: 26 mg/kg bw/day

Fatty acids, C14-18 and C16-18-unsatd., maleated

EC No. 288-306-2 / CAS No. 85711-46-2

DNEL long-term dermal (systemic), Workers: 3,33 mg/kg

PNEC:

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/L

PNEC aquatic, marine water: 1 mg/L

PNEC aquatic, intermittent release: 100 mg/L

PNEC sediment, freshwater: 41,6 mg/kg

PNEC sediment, marine water: 4,17 mg/kg

PNEC, soil: 2,47 mg/kg

PNEC sewage treatment plant (STP): 100 mg/L

2-methylpropan-1-ol

Index No. 603-108-00-1 / EC No. 201-148-0 / CAS No. 78-83-1

PNEC aquatic, freshwater: 0,4 mg/L

PNEC aquatic, marine water: 0,04 mg/L

PNEC aquatic, intermittent release: 11 mg/L

PNEC sediment, freshwater: 1,52 mg/kg

PNEC sediment, marine water: 0,152 mg/kg

PNEC, soil: 0,0699 mg/kg

PNEC sewage treatment plant (STP): 10 mg/L

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

PNEC aquatic, freshwater: 140,9 mg/L

PNEC aquatic, marine water: 140,9 mg/L

PNEC sediment, freshwater: 552 mg/kg

PNEC sediment, marine water: 552 mg/kg

PNEC, soil: 28 mg/kg

PNEC sewage treatment plant (STP): 2251 mg/L

PNEC water, intermittent release: 140,9 mg/L

Fatty acids, C14-18 and C16-18-unsatd., maleated

EC No. 288-306-2 / CAS No. 85711-46-2

PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 6 / 11

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Colour: yellow

Odour: characteristic

Odour threshold: not applicable

pH at 20 °C: not applicable

Melting point/freezing point: not applicable

Initial boiling point and boiling range: 78 °C

Source: Ethanol

Flash point: 37 °C

Evaporation rate: not applicable

flammability

Burning time: not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 1,59 Vol-%

Upper explosion limit: 15 Vol-%

Source: Ethanol

Vapour pressure at 20 °C: 8 mbar

Method: calculated.

Vapour density: not applicable

Relative density:

Density at 20 °C: 1,00 g/cm³

Solubility(ies):

Water solubility at 20 °C: partially soluble

Partition coefficient: n-octanol/water: see section 12

Auto-ignition temperature: 270 °C

Source: 1-methoxy-2-propanol

Decomposition temperature: not applicable

Viscosity at 20 °C: 40 s 4 mm

Method: DIN 53211

Explosive properties: not applicable

Oxidising properties: not applicable

9.2. Other information

Solvent separation test: < 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 7 / 11

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

2-methylpropan-1-ol

oral, LD50, Rat: 2460 mg/kg
dermal, LD50, Rabbit: 4200 mg/kg
inhalative (Gases), LC50, Rat: 6,5 ppmV (4 h)

propan-2-ol

oral, LD50, Rat: 4570 mg/kg
dermal, LD50, Rabbit: 13400 mg/kg
inhalative (vapours), LC50, Rat: 30 mg/L (4 h)

phthalic anhydride

oral, LD50, Rat: 1530 mg/kg
dermal, LD50, Rabbit: 3160 mg/kg
inhalative, Rat: 0,21 mg/L (1 h)

Ethanol

oral, LD50, Rat: 5000 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 10000 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat (4 h)
Method: OECD 401

Fatty acids, C14-18 and C16-18-unsatd., maleated

oral, LD50, Rat: > 2000 mg/kg
Method: OECD 423
female

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye damage.

2-methylpropan-1-ol

Skin (4 h)
Irritating to skin and mucosa
eyes: Evaluation strong caustic effect involving danger of serious eye damages

propan-2-ol

eyes
Skin

phthalic anhydride

Skin (4 h)
eyes

Ethanol

eyes

Respiratory or skin sensitisation

phthalic anhydride

Skin:
Respiratory system:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

propan-2-ol

Germ cell mutagenicity; Evaluation Non-mutagenic

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 8 / 11

1-methoxy-2-propanol
Specific target organ toxicity (single exposure), drowsiness

2-methylpropan-1-ol
Specific target organ toxicity (single exposure), Irritation
Specific target organ toxicity (single exposure), drowsiness

phthalic anhydride
Specific target organ toxicity (single exposure), Irritation

Aspiration hazard

propan-2-ol
Aspiration hazard; Evaluation While swallowing or vomiting, pulmonary aspiration may cause chemical pneumonitis, leading to death

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
There is no information available on the preparation itself.
Do not allow to enter into surface water or drains.

12.1. Toxicity

2-methylpropan-1-ol
Fish toxicity, LC50, *Leuciscus idus* (golden orfe): 1520 mg/L (96 h)
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 1250 mg/L (48 h)
Bacteria toxicity, EC50, *Pseudomonas putida*: 280 mg/L

propan-2-ol
Algae toxicity, EC50, *Scenedesmus subspicatus*: > 1000 mg/L (72 h)
Algae toxicity, EC50: > 100 mg/L
Fish toxicity, EC50: > 100 mg/L
Daphnia toxicity, EC50: > 100 mg/L

Ethanol
Fish toxicity, LC50, *Alburnus alburnus* (alburnum): 1100 mg/L (96 h)
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea) 9268 - 14221 mg/L (48 h)
Fish toxicity, *Leuciscus idus* (golden orfe): 8150 (48 h)
Algae toxicity, *Scenedesmus quadricauda*: 5000 (168 h)

Fatty acids, C14-18 and C16-18-unsatd., maleated
Fish toxicity, LC50, *Leuciscus idus* (golden orfe): > 150 mg/L (96 h); Evaluation static test
Method: DIN 38412
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): > 100 mg/L (48 h); Evaluation semistatic
Method: OECD 202
Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: > 100 mg/L ; Evaluation semistatic
Method: OECD 201
Bacteria toxicity, EC50, Activated sludge: > 1000 mg/L (3 h); Evaluation static test
Method: OECD 209

Long-term Ecotoxicity

propan-2-ol
Fish toxicity, LC50, *Pimephales promelas*: 9640 mg/L (96 h)
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 13299 mg/L (48 h)
Algae toxicity, EC50, *Desmodesmus subspicatus*: > 1000 mg/L (96 h)
Fish toxicity, LC50, *Pimephales promelas*: 11130 mg/L (96 h)

12.2. Persistence and degradability

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 9 / 11

propan-2-ol
, BOD (% of COD): 62 % ; Evaluation Biodegradable.
: 2,32 g oxigen/kg

12.3. Bioaccumulative potential

propan-2-ol
Partition coefficient: n-octanol/water: -0,16
phthalic anhydride
Partition coefficient: n-octanol/water: 1,6

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196
Print date: 09.07.2021
Version: 1.0001

Classic XD 50 semigloss
Revision date: 09.07.2021
Issue date: 08.03.2021

59345 EN
Page 10 / 11

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Category: P5c FLAMMABLE LIQUIDS
Quantity 1: 5000 t / Quantity 2: 50000 t

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 486
VOC-value (in g/L) ASTM D2369: 511

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/j) ; VOC limit value: 500 g/l
Maximum VOC content (g/L) of the product in a ready to use condition: 507

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other information:

Denmark:
MAL-Kode (MAL Kode ready-to-use):
Switzerland:
Volatile organic compounds (VOC) content in percent by weight: 48

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Full text of classification in section 3

| | | |
|----------------------|-----------------------------------|--|
| Flam. Liq. 3 / H226 | Flammable liquids | Flammable liquid and vapour. |
| STOT SE 3 / H336 | STOT-single exposure | May cause drowsiness or dizziness. |
| STOT SE 3 / H335 | STOT-single exposure | May cause respiratory irritation. |
| Skin Irrit. 2 / H315 | Skin corrosion/irritation | Causes skin irritation. |
| Eye Dam. 1 / H318 | Serious eye damage/eye irritation | Causes serious eye damage. |
| Flam. Liq. 2 / H225 | Flammable liquids | Highly flammable liquid and vapour. |
| Eye Irrit. 2 / H319 | Serious eye damage/eye irritation | Causes serious eye irritation. |
| STOT RE 2 / H373 | STOT-repeated exposure | May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| Skin Sens. 1 / H317 | Respiratory or skin sensitisation | May cause an allergic skin reaction. |
| Acute Tox. 4 / H302 | Acute toxicity (oral) | Harmful if swallowed. |
| Resp. Sens. 1 / H334 | Respiratory or skin sensitisation | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

| | | |
|---------------|-----------------------------------|------------------------|
| Flam. Liq. 3 | Flammable liquids | On basis of test data. |
| Skin Irrit. 2 | Skin corrosion/irritation | Calculation method. |
| Eye Dam. 1 | Serious eye damage/eye irritation | Calculation method. |
| STOT SE 3 | STOT-single exposure | Calculation method. |

Abbreviations and acronyms

| | |
|-----|---|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| OEL | Occupational Exposure Limit Value |
| BLV | Biological Limit Value |
| CAS | Chemical Abstracts Service |
| CLP | Classification, Labelling and Packaging |
| CMR | Carcinogenic, Mutagenic and Reprotoxic |

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 486196 Classic XD 50 semigloss
Print date: 09.07.2021 Revision date: 09.07.2021
Version: 1.0001 Issue date: 08.03.2021
59345 EN
Page 11 / 11

| | |
|-----------|---|
| DIN | German Institute for Standardization / German industrial standard |
| DNEL | Derived No-Effect Level |
| EAKV | European Waste Catalogue Directive |
| EC | Effective Concentration |
| EC | European Community |
| EN | European Standard |
| IATA-DGR | International Air Transport Association – Dangerous Goods Regulations |
| IBC Code | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk |
| ICAO-TI | International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air |
| IMDG Code | International Maritime Code for Dangerous Goods |
| ISO | International Organization for Standardization |
| LC | Lethal Concentration |
| LD | Lethal Dose |
| MARPOL | Maritime Pollution: The International Convention for the Prevention of Pollution from Ships |
| OECD | Organisation for Economic Cooperation and Development |
| PBT | persistent, bioaccumulative, toxic |
| PNEC | Predicted No Effect Concentration |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| UN | United Nations |
| VOC | Volatile Organic Compounds |
| vPvB | very persistent and very bioaccumulative |

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.