Revision: 15.12.2021

Printing date 15.12.2021

Version number 1.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
 - · Trade name: Urethane 20 XD
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC10 Roller application or brushing
- · Technical function Plating agent
- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

Synteko AB Olof Wijksväg 9

010) Wijksvag 9 444 65 Jörlanda, SWEDEN Office: +46 303 56 330 Mobile: +372 53 540 588

- · Further information obtainable from: -
- · 1.4 Emergency telephone number: -

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
 - · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
 - · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

- · Signal word Warning
- · Hazard-determining components of labelling:

Hydrocarbons, C9-11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Fatty acids, C-18 unsaturated, dimers, reaction products with N-n-dimethyl-1,3- propanediamine and 1,3- propanediamine

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Revision: 15.12.2021

Printing date 15.12.2021 Version number 1.4

Trade name: Urethane 20 XD

(Contd. of page 1)	
P103 Read carefully and follow all instructions.	P10.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.	P216
No smoking.	
P240 Ground and bond container and receiving equipment.	P24
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.	P24
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.	P26
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	P28
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	P30.
P405 Store locked up.	P40.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.	P50

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
 - · Results of PBT and vPvB assessment
 - · **PBT**: Not applicable.
 - · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64742-48-9	Hydrocarbons, C9-11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	<i>>25</i> –≤ <i>50</i> %	
EC number: 919-857-5	🊸 Flam. Liq. 3, H226; 🗞 Asp. Tox. 1, H304; ∿ STOT SE 3, H336		
CAS: 85203-81-2	Hexanoic acid, 2-ethyl, zinc salt, basic	≤2.5%	
EINECS: 286-272-3	♦ Repr. 2, H361fd; ♦ Eye Irrit. 2, H319; Aquatic Chronic 3, H412		
CAS: 2457-02-5	Strontium bis(2-ethylhexanoate)	≥0-<1%	
EINECS: 219-536-3	 Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. H315 		
CAS: 162627-17-0	Fatty acids, C-18 unsaturated, dimers, reaction products with N-n-dimethyl-	≤0.25%	
EC number: 605-296-0	1,3- propanediamine and 1,3- propanediamine		
	💠 Skin Sens. 1A, H317		
· Regulation (EC) No 648/2004 on detergents / Labelling for contents			

aliphatic hydrocarbons ≥30%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - · General information: Immediately remove any clothing soiled by the product.
 - · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 15.12.2021 Revision: 15.12.2021 Version number 1.4

Trade name: Urethane 20 XD

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
 - · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
 - · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
 - · Storage:
 - Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Store in a cool location.

No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
 - · Additional information about design of technical facilities: No further data; see item 7.
 - · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
 - · Personal protective equipment:
 - General protective and hygienic measures:

Do not eat or drink while working.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 4)

Printing date 15.12.2021 Version number 1.4 Revision: 15.12.2021

Trade name: Urethane 20 XD

(Contd. of page 3)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



CECTION O. Dissers and and also

· Upper:

· Vapour pressure at 20 °C:

Tightly sealed goggles

· **Body protection:** Protective work clothing

<u> </u>	SECTION 9: Physical and chemical properties			
9.1 Information on basic physical and chem	ical properties			
General Information Appearance:				
· Appearance. · Form:	Fluid			
Colour:	Violet			
· Odour:	Specific type			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
· Melting point/freezing point:	Undetermined.			
· Initial boiling point and boilin	g range: 180 °C			
· Flash point:	31 °C			
· Flammability (solid, gas):	Not applicable.			
· Decomposition temperature:	Not determined.			
· Auto-ignition temperature:	Product is not selfigniting.			
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.			
· Explosion limits:				
· Lower:	0.6 Vol %			

7 Vol %

1 hPa

(Contd. on page 5)

Printing date 15.12.2021 Version number 1.4 Revision: 15.12.2021

Trade name: Urethane 20 XD

		(Contd. of page 4)
· Density at 20 °C:	~0.91 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/wate	er: Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C:	70 s (DIN 53211/4)	
· Solvent content:		
· VOC (EC)	53.40 %	
· Solids content:	44.6 %	
• 9.2 Other information No	further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
 - · Acute toxicity Based on available data, the classification criteria are not met.
 - · Primary irritant effect:
 - · Skin corrosion/irritation Based on available data, the classification criteria are not met.
 - · Serious eye damage/irritation Based on available data, the classification criteria are not met.
 - · Respiratory or skin sensitisation
 - May cause an allergic skin reaction.
 - · Additional toxicological information:
 - · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 - · Germ cell mutagenicity Based on available data, the classification criteria are not met.
 - · Carcinogenicity Based on available data, the classification criteria are not met.
 - · Reproductive toxicity Based on available data, the classification criteria are not met.
 - · STOT-single exposure
 - May cause drowsiness or dizziness.
 - · STOT-repeated exposure Based on available data, the classification criteria are not met.
 - · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
 - · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

Revision: 15.12.2021 **Printing date 15.12.2021** Version number 1.4

Trade name: Urethane 20 XD

(Contd. of page 5)

- · Additional ecological information:
 - · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
 - · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
14.1 UN-Number		
· ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
$\cdot ADR$	1263 PAINT	
· IMDG	PAINT	
· IATA	Paint	
14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class	2 Element le l'enide	
· Class · Lahel	3 Flammable liquids. 3	
	<u> </u>	
14.4 Packing group		
· ADR, IMDG, IATA	III	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Warning: Flammable liquids.	
· Hazard identification number (Kemler		
· EMS Number:	F-E, <u>S-E</u>	
· Stowage Category	A	
14.7 Transport in bulk according to Annex II of Mar		
and the IBC Code	Not applicable.	
· Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	5L	
· Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per	inn
	packaging: 30 ml	
	Maximum net quantity per	oui
To see and a set a set a sec	packaging: 1000 ml	
· Transport category	3	

Printing date 15.12.2021 Version number 1.4 Revision: 15.12.2021

Trade name: Urethane 20 XD

	(Contd. of page 6)
· Tunnel restriction code	D/E
\cdot IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Directive 2012/18/EU
 - · Named dangerous substances ANNEX I None of the ingredients is listed.
 - · Seveso category P5c FLAMMABLE LIQUIDS
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
 - · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity - Category 2

(Contd. on page 8)

Printing date 15.12.2021 Revision: 15.12.2021 Version number 1.4

Trade name: Urethane 20 XD

(Contd. of page 7)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.