

SYNTEKO EXTENDER



Synteko EXTENDER is an additive for Synteko waterborne lacquers. It improves levelling and prolongs working time for both primers and top coats. Adding 2% of EXTENDER reduces the tendency for roller marks or discoloring in bad indoor climate conditions (high temperatures, low humidity or in large areas).

TECHNICAL DATA:

Properties	for all Synteko waterborne lacquers (primers or top coats)
Package size	100 ml plastic bottle
Storage, shelf life	24 months in unopened container from production date. Best to be stored between + 5° až + 25° C Keep out of the range of children.
Cleaning	clean tools with water immediately after use
Disposal	never pour surplus finish down the drains. Dispose it in accordance to local regulations.

DIRECTION FOR USE

- Add 2% Extender to the waterborne primer or top coat and shake/stir well.
- If using 2 component systems add extender before adding the hardener.
- Do not use below +14°C

HEALTH AND ENVIRONMENT

Use the normal due care when handling chemical products. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Safety Data Sheet.

Producer:
Synteko AB
info@synteko.com
+46 303 563 30
Olof Wiksväg 9, 444 65 Jörlanda, Sweden