

SYNTEKO ADDITIVE



Synteko WHITE ADDITIVE is an pigment for Synteko waterborne lacquers.

TECHNICAL DATA:

Properties	for all Synteko waterborne lacquers (primers or top coats)
Package size	80 ml plastic bottle
Storage, shelf life	12 months in unopened container from production date. Best to be stored between + 5° až + 25° C Keep out of the range of children.
Cleaning	clean tools with water immediately after use
Disposal	never pour surplus finish down the drains. Dispose it in accordance to local regulations.

DIRECTION FOR USE

- Shake thoroughly so that the individual components mix, mix with the finish and apply according to the recommendations of the individual water-based varnishes.
- Add to the finish just before application.
- Dosage max. 1x80 ml up to 5L.
- In the case of using pigment in 2-component varnishes, the pigment is added only after mixing the varnish with hardener, not before!
- In case of use in 1-component varnishes, the varnish must be processed within 24 hours; For 2-component varnishes, processing must take place within 4 hours
- The pigment can be applied to the first layer of topcoat as well as to subsequent layers. We recommend that you always test for the desired coloration.

HEALTH AND ENVIRONMENT

Use the normal due care when handling chemical products. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Safety Data Sheet.

Producer:
Synteko AB
info@synteko.com
+46 303 563 30

Olof Wiksväg 9, 444 65 Jörlanda, Sweden

www.synteko.com