



SYNTEKO NORDIC ELASTIC REFRESHER

Synteko Nordic Elastic REFRESHER renews shine and protects finished LVT, vinyl, PVC, linoleum and rubber

AREA OF USE:

for residential and commercial areas

PRODUCT PROPERTIES:

- Easy to use
- Easy to apply
- Very low VOC
- Quick drying, fully cured within 1 hour
- Coverage ca 50m²/l

TECHNICAL DATA:

Base material	Copolymer acrylate, ammonia solution less than 1%
VOC	41 g/L
pH	Approx. 8,5
Shelf life	36 months in unopened container from production date (see package)
Storage	Store frost-free. Must be stored between +5°C and +30°C.
Package size	1L, 5L

DIRECTIONS FOR USE

1. Floors that have previously been treated with polish or wax must be deep cleaned with REMOVER before using REFRESHER
2. Apply REFRESHER undiluted directly onto the floor, spread with the clean damp mop or lint-free cloth
3. Allow to dry for approx. 1 hour, after this time the floor is ready for use

HEALTH & SAFETY INFORMATION

Safety data sheet available for professional user on request. Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet), available on www.synteko.com. The following only represents a selection of important information.

Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.